


MF 2400



- ❑ **Three models, all with 4-wheel drive as standard**
- ❑ **Latest generation Perkins 800 Series engines provide excellent performance, economy and renowned reliability**
- ❑ **Range of transmissions to include 200 m/hr Supercreep and Speedshift to suit both municipal and agricultural requirements**
- ❑ **New standards of operator comfort from totally new cab design**
- ❑ **High performance hydraulics with two-speed PTO as standard**
- ❑ **Suitable for a wide range of farming, horticultural, grounds care and municipal applications**
- ❑ **Standard (ST) and Ground Effect (GE) versions: the GE has lower overall height giving added stability and improved access to low buildings**
- ❑ **Unrivalled dealer service and back-up**

Pictures may show variable equipment

New 'Utility' tractors
3 models: 66 to 82 hp




MASSEY FERGUSON

MF 2400 Specifications: ● = Standard ○ = Optional

		MF 2430 ST	MF 2430 GE	MF 2435 ST	MF 2435 GE	MF 2440 ST	MF 2440 GE
Engine power							
@ 2500 rev/min	* ISO hp (kW)	66 (49)	66 (49)	76 (56)	76 (56)	82 (60)	82 (60)
Max. torque @ rev/min	* Nm	210 @ 1600	210 @ 1600	235 @ 1600	235 @ 1600	253 @ 1600	253 @ 1600
* ISO TRI4396							
Engine							
Water cooled, direct injection diesel	make type	Perkins 800 Series	Perkins 800 Series	Perkins 800 Series	Perkins 800 Series	Perkins 800 Series	Perkins 800 Series
Aspiration		Turbo	Turbo	Turbo	Turbo	Turbo	Turbo
Capacity	litre	3.3	3.3	3.3	3.3	3.3	3.3
Transmission							
15/15 (40 km/h) synchro shuttle		●	●	●	●	●	●
30/30 synchro shuttle, plus creep		○	○	○	○	○	○
30/30 synchro shuttle with two-stage speedshift		○	○	○	○	○	○
60/60 synchro shuttle with two-stage speedshift plus 0.2 km/h creeper		○	○	○	○	○	○
Linkage and hydraulics							
Mechanical linkage control		●	●	●	●	●	●
Electronic linkage control		○	○	○	○	○	○
Maximum available oil flow	litre/min	57	57	57	57	57	57
Maximum lift capacity, at link ends, links horizontal	kg ●	2100	2100	2100	2100	2100	2100
	kg ○	3400	3400	3400	3400	3400	3400
Power take-off							
Systems available		Independent and in-cab shiftable, 540/540E, 540/1000 rev/min and proportional ground speed					
Wheels and tyres							
Front		12.4R24	320/70R20	12.4R24	320/70R20	12.4R24	320/70R20
Rear		14.9R30	14.9R28	14.9R30	14.9R28	14.9R30	14.9R28
Cab and controls							
Standard equipment includes: De-luxe 'flat floor' cab, side exhaust, tinted glass, opening front and rear windows, rear windscreen wash/wipe, glass roof panel, three-speed blower with heater unit, mechanical seat, provision for radio cassette player, 2 spool valves, 2 front and 2 rear work lights.							
Variable equipment includes: Full air conditioning, pneumatic seat, passenger seat, 1 or 2 additional spool valves, right-hand hydraulic levelling.							
Weights and dimensions (approximate, less fuel)							
Weight	kg	3050	2850	3050	2850	3050	2850
Length, links horizontal	m	4.02	3.99	4.02	3.99	4.02	3.99
Height, over cab	m	2.44	2.38	2.44	2.38	2.44	2.38
Wheelbase	m	2.16	2.13	2.16	2.13	2.16	2.13
Fuel tank capacity	litre	90	90	90	90	90	90

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

www.masseyferguson.com



MASSEY FERGUSON

MASSEY FERGUSON is a worldwide brand of AGCO Corporation
© AGCO Limited. 2004 | English/0804/15m | 13328/0804/70m

